

# ROBUST. RELIABLE. RESILIENT.

## Introducing Our New Underlayment



**SECURE ROOF  
COMPONENTS™**  
by Eagle Roofing Products

# SECURE GUARD 60™

*In partnership with our friends at G.A.P. Roofing, Inc., Secure Guard 60 is a polyester-reinforced, non-woven surfaced underlayment designed for steep slope tile and metal applications.*

Equipped with incredible durability and strength, **Secure Guard 60** delivers excellent bonding and material fortitude while protecting homes and commercial buildings from extreme weather conditions like blazing heat, torrential rains, powerful winds and beyond.

The optimal choice for a formidable, cost-effective solution, **Secure Guard 60** features a:

- strong 60 mil material that seals better around screws and holds up to traffic
- split release film for quick and seamless application
- roll size that covers 2 squares of roof area
- plastic wrap for minimal trash at job sites
- 30 Year Limited Warranty provided by G.A.P
- 180-day UV exposure period

In addition, it:

- is suited for Concrete Tile Roofs, Clay Tile Roofs, as well as Mechanically Fastened Roof Systems
- is listed as an approved underlayment by most tile foam adhesive manufacturers for Tile Roof Adhesive Systems
- is temperature resistant to 265°F, making it ideal for Metal Roofing Systems
- is designed to be an air, water and vapor barrier
- is an ideal product to use on critical roof areas
- is ASTM E108 and UL 790 Tested: Class A Assembly under Eagle Concrete Roof Tiles
- is made in North America adhering to U.S. standards using safe components



*Choose peace of mind with a dependable shield that provides complete protection against the elements.*

connect with us!



[eagleroofing.com](http://eagleroofing.com)

USA Owned. USA Made.



# Forge Resilient Roofs with an Underlayment You Can Rely On



## SECURE GUARD 60™

*Crafted for high temperature applications under adhesive-bonded tile roofs as well as metal and mechanically attached systems, Secure Guard 60\* is an outstanding underlayment that provides utmost protection from ice, rain, wind and fire. Manufactured to last, Secure Guard 60 is easy to install while remaining remarkably strong and enduring.*



### TECHNICAL DESCRIPTION PROVIDED BY G.A.P.

Material Performanc	ASTM Method	Results
Maximum Load MD/CD min	D2523/D1970	≥ 25 lbf/in
Elongation at Break	D2523/D1970	≥ 10%
Adhesion to Plywood, min @ 40°F	D903/1970	≥ 2.0 lbf/ft
Adhesion to Plywood, min @ 75°F	D903/D1970	≥ 12.0 lbf/ft
Low Temperature Flexibility, max	D1970	Pass
Tear Resistnace MD/CD, min	D4073/D1970	≥ 20 lbf
Moisture Vapor Permeance	E96	≥ 0.1 U.S. perms
Sealability Around Nail	D1970/D7349	Pass
Waterproof Integrity After Low-Temp Flexibility	D1970	Pass
Waterproof Integrity of Lap Seam	D1970/D7349	Pass

### DATA (ASTM Specification D1970)

Rolls per Pallet	25
Weight per Roll	Approx. 68 lbs (nom)
Roll Size	39 3/8" x66'
Thickness	60 mils
Coverage	2 Square

### APPLICABLE STANDARDS

- ASTM 1970
- ASTM E108
- Florida Building Code
- Miami-Dade Approved
- Texas Department of Insurance



**For more information and to register the 30 Year Limited Warranty associated with Secure Guard 60 by G.A.P. Roofing, Inc., visit: [eaglerooftng.com/secure-guard-60](http://eaglerooftng.com/secure-guard-60)**

*\*Secure Guard 60 is a product of Eagle Roofing Products "Secure Roof Components" line.*

connect with us!



[eaglerooftng.com](http://eaglerooftng.com)

USA Owned. USA Made.

