

FORTIFY YOUR PROPERTY WITH THE ULTIMATE CLASS A FIRE RESISTANT UNDERLAYMENT



**SECURE ROOF
COMPONENTS™**
by Eagle Roofing Products

VALOR THERMAL™
BY SOLRSKIN

Introducing Valor Thermal by Sol-R-Skin™: a groundbreaking roofing underlayment that embodies the thermal and fire-resistant qualities of high-performance insulation while providing premium protection against extreme weather.



**Highest resistance to fire
when installed with concrete
or clay tile roofing**



Valor Thermal is comprised of layers of 99% highly polished, scrim reinforced aluminum, thin, insulative fiberglass, and synthetic underlayment. The result? A product that is revolutionizing the roofing market and helping roofers meet new fire and energy codes.

- Ideal for use under Concrete Tile Roofs, Clay Tile Roofs and Stone Coated Steel
- 1200°F melting point
- Compliant with ASTM E -108 Burning Brand Test
- Helpful for meeting California's Title 24 regional requirements
- Listed with California's Office of the State Fire Marshal for use in fire resistant roof systems in Wildland Urban Interface (WUI) regions

Choose peace of mind with the premium fire-resistant qualities of Valor Thermal—protection you can trust, season after season.

connect with us!



eagleroofting.com



More Than Fire Resistance

EXPERIENCE PREMIER ENERGY EFFICIENCY

Valor Thermal by Sol-R-Skin™ uses patent-pending technology to seamlessly integrate premium weather protection with energy efficiency benefits.

With one of the highest R values available on the market today (R 5.6) when installed with tiles fastened to standard battens, this fortified underlayment is incredibly effective at preventing thermal energy transfer into the attic space, which helps keep buildings cooler in the summer and warmer in the winter.



**SECURE ROOF
COMPONENTS™**
by Eagle Roofing Products

VALOR THERMAL™
BY SOLRSKIN



TEST DATA PROVIDED BY INTERNATIONAL INSULATION PRODUCTS, LLC

Thermal Performance

R 2.2 with tiles fastened Direct-to-Deck
R 5.6 with tiles fastened to Standard Battens*

ASTM C1363/C1224

Physical Properties

Burning Brand	Class A	ASTM E -108
Flame Spread	Class A	ASTM E 84-10a
Smoke Developed	Class 1	ASTM E 84-10a

Meets Or Exceeds ASTM D226 Type I & II, ASTM D1970 (7.7), ASTM E84
Complies with ASTM D 8257
Meets CalFire 4310-2283:0500
Florida Product Approval 27940
Miami-Dade County Approved NOA 18-0809.03



**May exceed R 5.6 with Eagle's Arched Battens, pending test results.*

For more information on the features and benefits of Valor Thermal by Sol-R-Skin™, visit: eagleroofting.com/valor-thermal

*Valor Thermal by Sol-R-Skin™ is a product of Eagle Roofing Products "Secure Roof Components" line. This product is a collaboration with Eagle Roofing Products and International Insulation Products, LLC.

connect with us!



eagleroofting.com

